



## EQQY2.MH15585 Casting Impregnation Materials - Component

[Page Bottom](#)

---

### Casting Impregnation Materials - Component

[See General Information for Casting Impregnation Materials - Component](#)

**HENKEL CORP**

MH15585

ONE HENKEL WAY  
ROCKY HILL, CT 06067 USA

**Casting impregnation material**, Resinol RTC, 90C, for exposure to gasoline, kerosene, fuel oils, naptha and gasoline/ethanol and gasoline/methanol mixtures with a maximum of 15% ethanol or methanol.

PMS-10E, for exposure to gasoline, kerosene, naptha and fuel oils.

PMS-50E, for exposure to gasoline, kerosene, fuel oils, naptha and alcohol-blended gasoline mixtures with concentrations with a maximum of 15 % ethanol or methanol.

Marking: Company name and material designation.

[Last Updated](#) on 2010-07-14

---

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2010 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

